

ASSOCIATED SPECIFICATIONS CHART

ASSOCIATED



Safe In Any Weather



Made in USA



	Commercial Duty Charger	Heavy Duty Charger	Heavy Duty Fleet Charger/Analyzer	Intellamatic® Charger and Re-flash Power Supply			
	SKU 221248 ASC6002B	SKU 662763 ASC6012AGM	SKU 1414394 ASC6021AGM	SKU 343370 ASC6007B	SKU 344790 ASC6008	SKU 343379 ASC6008MSK	SKU 662745 ASCIBC6008MSK
Continuous Amperage Charging Rate	100/80A	70/60A	70/65/30	40A	60A	60A	60A
Re-Flash Power Supply Output Amperage	N/A	N/A	N/A	45A	70A	70A	70A
UL Boost Rating	400A	250A	205	130A	270A	270A	270A
Operating Charging Voltage	6/12/18/24V	6/12V	6/12/24V	12V	12V	12V	12V
Battery Types	3	4	4	5	5	5	6
Indoor/Outdoor Rated	Y	Y	Y	Y	Y	Y	Y
Smart Charger/Battery Diagnostics	N	N	N	Y	Y	Y	Y
Adjustable Charging Voltage	N	N	N	N	N	N	Y
Adjustable Charging Amperage	N	N	N	N	N	N	Y
Adjustable Re-Flash Power Supply Voltage	N	N	N	N	N	N	Y
Polarity Indicated/Protected	Y	N	N	Y	Y	Y	Y
Memory Saver Mode	N	N	N	N	N	Y	Y
DC Cable Length and Gage	8' 4AWG	6-1/2' 6-1/2AWG	6-1/2' 4AWG	6-1/2' 6-1/2AWG	6-1/2' 4AWG	6-1/2' 4AWG	6-1/2' 4AWG
Clamp Rating	500A	400A	400A	400A	400A	400A	400A
A/C Cord Length	10' 14-3	6-1/2' 16-3	6.5' 16-3	6' 18-3	6' 16-3	6' 16-3	6' 16-3
Weight (Pounds) Lb.	70	48	56	47	47	47	48
Dimensions (LxWxH)	17.25 x 16.5 x 30"	17.25 x 16.5 x 26.5"	17.25 x 16.5 x 26.5"	17.25 x 16.5 x 26.5"	17.25 x 16.5 x 26.5"	17.25 x 16.5 x 26.5"	17.25 x 16.5 x 26.5"
Warranty	1	1	1	2	2	2	2
COO	US ⁷	US ⁷	US ⁷	US ⁷	US ⁷	US ⁷	US ⁷

¹ Two Year Bumper to Bumper and 5 Year on Transformer and Rectifier

² Two Year Bumper to Bumper and 3 Year on Transformer and Rectifier

³ SLA

⁴ SLA, AGM

⁵ SLA, AGM, Gel-Cell

⁶ SLA, AGM, EFB, Lithium-Ion, Gel-Cell

⁷ Made in the USA with US and Globally Sourced Parts.



Order today! Call your Commercial Sales Manager or order online at AutoZonePro.com.