













Factor in unstable fuel prices and escalating disposal costs and you'll see why purchasing a Lanair XT Series Heater is indeed "The Right Choice at the Right Time!"

The XT-200 Waste Oil Heater now burns 100% used synthetic oil and comes standard with an easy access hinged chamber door for easy clean out. It also features a large clean-out side-access panel to the collector box. Some of the new improvements made to the XT models are: easy to remove burner, a noncontinuous spark transformer, an hour meter, and a prime switch. All of these features make it easy for those who compare...buy Lanair!

# XT-200

### **WASTE OIL HEATER**



## HOW MUCH IS YOUR USED OIL WORTH?

Use our savings calculator on lanair.com to find out how much green you will save while protecting the environment.



#### **PRODUCT SPECIFICATIONS**

Heat Range (BTUH)*	Up to 200,000
Fuel Input (GPH)	1.4
Fuel Type <sup>†</sup>	Used crankcase oil up to 50 wt (conventional or synthetic), used automatic transmission fluid, #1 and #2 fuel oil (diesel)
Heating Area (sq. ft.)**	Up to 5,000
Power Supply (AC)***	120 V-60Hz 20 Amps
Cabinet Dimensions (L x W x H)	48" x 40" x 24"
Hanging Weight (lbs.)	453
Axial Fan (CFM)	2,600
Chimney Pipe****	6" Class A
Compressed Air****	2 CFM – 12-15 PSI
Combustion Chamber	12 Gauge CRS
Ductable Option	No
Chimney Location	Top and side

<sup>\*</sup> BTUH value varies with fuel type.

Hazardous waste is illegal to burn in a waste oil heater.

The EPA of the USA does not allow the burning of brake fluid, and it is illegal to burn in a waste oil heater.

There is no UL safety standard for the burning of used cooking oil (vegetable oil) at this time. It should not be burned.

Note: International customers should check their local regulations, as "what you can legally burn" may change.

### Lifetime Tech Support (via phone)

Lanair App

1-Year/10-Year Limited Warranty (parts/chamber)
UL and ULC Listed

















<sup>\*\*</sup> The suggested heating area is based on building with minimal heat loss due to open door, construction, materials, windows, insulation, etc.

<sup>\*\*\*</sup> With optional compressor 30 amp breaker with 10 gauge wire is required.

<sup>\*\*\*\*</sup> Chimney package sold separately.

<sup>\*\*\*\*\*\*</sup> Customer supplied. Air source must be capable of producing 2.0 CFM @ 30 PSI to secondary air filter regulator.

 $<sup>^\</sup>dagger \text{Stay away from gear lubes. They do not burn and will cause additional maintenance for your waste oil heater.}$